

DUKERS DCB48-D2



Brand: DUKERS

Product Code: DCB48-D2

Availability: In Stock

Weight: 0.00lb

Dimensions: 48.13in x 32.25in x 26.63in

Price: \$2,153.00

Short Description

Dukers DCB48-D2 Chef Base Refrigerator with 2 Drawers

Description

Product Features

- Digital temperature control features a digital display to make monitoring interior temperatures a breeze. This unit also comes with an auto-defrost function
- Foamed-in-place insulation keeps the interior cold and adds structural strength
- Stainless steel interior with rounded corners for easy cleaning. Meets and exceeds sanitation standards.
- Durable and high weight bearing rails for drawers.
- Heavy-duty 4" casters with brakes are included providing the unit with convenient mobility, making cleaning and servicing a breeze! Just roll the unit away from the wall.
- Ergonomic and modern recess door handles.
- Removable Drawer Gaskets, each drawer gasket is removable for easy cleaning and maintenance.
- Warranty for commercial use only. No warranty for residential use.

Specifications

Technical Specifications

x000D

x000D

- Refrigerant: R290/1.76oz
- Commercial use only
- Top/Bottom Drawers
- Dimensions (W x D x H): 48" x 32 1/4" x 26 5/8"
- Temperature range: 33~38°F
- Freezer Casters (4")
- Stainless Steel interior and exterior
- Voltage/Frequency: 115V/60HZ
- Refrigerant: R290/1.76oz
- Type of Defrost: Automatic
- Interior Material: 304/201 Stainless Steel
- Exterior Material: 304/201 Stainless Steel
- Total Current: 1.7A
- Climate Category: 4/5
- Refrigerant: R290/1.76oz
- NEMA Config: NEMA 5-15P

Shipping / Pick Up

Free Shipping On Certain Orders! Call Now For a Quote!

Warranty

Warranty for commercial use only. No warranty for residential use.

Product Gallery

DETAILS & SPECIFICATIONS

CHIEF BASE

Side View

MODEL 32348

Model Voltage	115V
Model Frequency	60Hz
Total Input Power	2400W
Rated Capacity	1.1kVA
Climate Category	1
Protection Type	IP20

Design Protection Index (IP): IP20/20

Design Protection Level (DPL)	10/10
Maximum Working Life	1.44million
Surge Voltage	16kVrms
Surge Current	40000A @ 10/100
Temperature Range	31~54°C
Working Power	1500W
AC-DC Converter Efficiency	94%
Efficiency (Load)	92.5% @ 1/10
100Hz Mode	0

HALF PICO

FULL PICO

Full Load

SIXTH PICO

Los Angeles | San Francisco | Dallas
Houston | Phoenix | Charlotte | New Jersey

1-800-421-0323

info@dukersusa.com

www.dukersusa.com

DUKERS
Quality Commercial Refrigeration

3 YEAR WARRANTY

CHEF BASE MODEL DCS-48

PRODUCT FEATURES

- 1) Digital temperature control features a digital display to make monitoring interior temperature easier. They also display units with all other without function.
- 2) Formed to force modulation helps the interior will not suffer structural damage.
- 3) Stainless steel interior with stainless surface for easy cleaning, wear and resistant corrosion materials.
- 4) Solid and high weight bearing lids for stability.
- 5) Interior 4" casters with wheels are included, making this unit use with convenient mobility, allowing moving and positioning convenient, just roll the unit across from the wall.
- 6) Long-term and rugged construction features.
- 7) Ergonomic Design: Stainless cast drawer handles is comfortable for easy handling and maintenance.

TECHNICAL SPECIFICATIONS

Capacity	48 cubic feet
Temperature	0°F to 10°F
Material	Stainless Steel
Interior Material	Stainless Steel
Shelf Material	Stainless Steel
Door Material	Stainless Steel
Door Locks	1/2"
Weight	450 lbs
Warranty	3 Year
Model	DCS-48

HIGH QUALITY STAINLESS STEEL & ROBUST DESIGN

DUKERS
Cooling Solutions | San Francisco | Dallas
Houston | Phoenix | Chicago | New Jersey

1-800-431-0633
info@dukersusa.com
www.DukersUSA.com

